

Energy and Mines





British Columbia Geological Survey Open File 2014-15 Geoscience BC Map 2014-06-10

Basal till potential of the Hulatt map area (NTS 093G/13), British Columbia

D. Sacco, T. Ferbey and W. Jackaman

Scale 1:50,000

Geology and data compilation by D. Sacco. Cartography by H. Arnold.

SURFICIAL GEOLOGY

NOTE: Where map units are composed of multiple surficial materials, a compound map unit designator is used, separating more extensive materials from less extensive (e.g., for Tb.Tv, Tb is more extensive than Tv).

ORGANIC DEPOSITS: Largely saturated organic materials, consisting mainly of mosses, sedges, or other hydrophytic vegetation.

Undifferentiated organic deposits: Bogs, fens, and swamps; generally where shallow lakes have been infilled and in depressions along floodplains and abandoned meltwater

GLACIOLACUSTRINE DEPOSITS: Well sorted, stratified sand, silt and clay deposited by suspension settling and interflow and underflow currents; diamictons released from floating ice or colluviated from valley sides into glacial lakes. Grain size may increase, and sorting may decrease, in ice proximal environments.

GLv Glaciolacustrine veneer: Deposits less than 2 m thick that conform to underlying topography; predominantly fine-grained material or silt-rich diamictons.

GLACIOFLUVIAL DEPOSITS: Poorly sorted to well sorted sand and gravel transported and deposited directly by glacial meltwater.

Gfv Glaciofluvial veneer: Deposits less than 2 m thick that conform to underlying topography.

GFr Eskers: Sinuous ridges of stratified sand and gravel deposited in subglacial, englacial, or

BASAL TILL DEPOSITS: Diamictons eroded, transported and deposited at the base of an active glacier. They are dense, massive and matrix supported. Matrix is typically composed of silt and clay with lesser amounts of sand. Clasts are often subangular to subrounded and can be faceted and

Tv Till veneer: Deposits less than 2 m thick that conform to underlying topography predominantly in upland regions with isolated bedrock exposures.

Tb Till blanket: Deposits greater than 2 m thick that mask subtle variations in substrate surface but generally conform to underlying topography; predominantly in areas of low relief.

Ts Streamlined till: Flutings, drumlins, and the sediment (down ice) part of crag-and-tails

ABLATION TILL DEPOSITS: Diamictons deposited by melt out, commonly from stagnant ice, of fartravelled supraglacial and englacial material. These deposits lack the density of basal till and have a high percentage of matrix sand. May be stratified and include sorted sands and gravels.

Undulating till: Loose, sandy diamicton commonly representing thinner deposits near the margins of widespread ice stagnation or in depressions where localized ice stagnation Th Hummocky till: Loose sandy diamicton commonly representing thicker deposits and

widespread ice stagnation. Consist of hillocks and hollows with slopes ≥ 15°.

BEDROCK: Lithology varies greatly across the map area and includes sedimentary, metamorphic, volcanic, and intrusive rocks of Permian to Quaternary age. Outcrop is generally limited to areas of

Undifferentiated bedrock: High-angle slopes in upland areas or in incised meltwater channels; may be susceptible to rock fall; hummocky, or undulating expressions are the result of glacial or meltwater erosion, or preferential erosion due to structural weaknesses;

FIELD STATIONS TILL SAMPLES (Labeled with sample number)

Fluted Bedrock

 Matrix geochemistry and mineralogy (Sacco et al., 2014) O (Sacco et al., 2014)

MINERAL OCCURRENCES

Provincial MINFILE database (Labeled with name and MINFILE number)

streamlined bedrock is the result of glacial erosion.

Developed Prospect

Showing


ICE-FLOW INDICATORS (Ferbey et al., 2013)

Unidirectional indicators **Bidirectional indicators** Drumlinoid or fluting

Fluted Bedrock

/// Provincial Parks

: Only thick basal till (Tb or Ts); may contain lesser amounts of thin basal till 2: Only thin basal till (Tv); may contain lesser amounts of thick basal till 3: Basal till with lesser amounts of another surficial material, excluding ablation till Basal till with lesser amounts of ablation till (Tb.Tu). Ablation till with lesser amounts of basal till (Tu.Tb). 6: Another surficial material with lesser amounts of basal till (e.g., Cb.Tb). : Only ablation till at surface (Th or Tu), or ablation till and another surficial material, excluding basal till (e.g., Th.GFc; GFb.Tu).



Universal Transverse Mercator Zone 10 North

DESCRIPTIVE NOTES

The Hulatt map area (NTS 093G/13) is in flat to gently rolling country the Interior Plateau physiographic region (Holland, 1976). Mainly drift covered, the area is thought to be underlain terrane (to the west) and Quesnel terrane (to the east). These two neighbouring island-arc assemblages have high potential for mineralization such as calc-alkalic Cu-Mo±Au and alkaline Cu-Au porphyries (Logan, 2013). Because of sparse outcrop, the area remains

Current work in the Hulatt map area is part of Geoscience BC's Targeting Resources for Exploration and Knowledge (TREK) project. Initiated in 2013, this project applies modern geochemical and geophysical methods to better understand the geology and mineral deposits of the area (Clifford and Hart, 2014; Sacco et al.,

LONGITUDINAL SECTION

ICE-FLOW DIRECTION

down-ice direction (light purple). Note how the head of a dispersal train is offset, in the down-

2014). This work builds on previous studies in the and geophysical investigations (Diakow et al., 1997; Struik and MacIntyre, 2001) and developing exploration techniques specific to drift-covered areas (Levson and Giles, 1997; Levson, 2001a).

The basal till potential map presented here is one of a series of 10 maps (see inset map) that were phases of the TREK geochemical program. Samples shown on these maps were collected for till matrix geochemical and mineralogical analysis; results will

The purpose of this basal till potential map series is to assist in the design of exploration projects, and to guide surficial sediment geochemistry and mineralogy sampling programs, by samples can likely be collected and areas where sampling will be difficult or require different geochemical sampling protocols. Ice flow indicators compiled by Ferbey et al. (2013) are included in the maps to illustrate the general transport directions of basal till.

This mapping builds on earlier drift exploration potential maps developed by Proudfoot et al. (1995). Map unit definitions are based on conventions outlined by Deblonde et al. (2012). Map unit colours depict the potential occurrence of basal till; map unit labels include surficial

> Existing surficial geology, terrain, or soils and landform mapping data were reviewed and updated using digital air photo stereo-pairs in DAT/EM Summit Evolution photogrammetry software running in tandem with Esri ArcMap. New mapping emphasized the till facies best suited for geochemical and mineralogical analysis. We focused on distinguishing basal till (Figure 2) from ablation till (Figure 3) which, because of a more complex transport and depositional history, is illsuited for mineral exploration. This differentiation was based largely on interpretations of air photo stereo-pairs supplemented by sparse field data.

Figure 1. Model of clastic dispersal in basal till (modified from Miller, 1984). Highest values (dark blue) define the head of a dispersal train at surface, and decrease exponentially in the ice-flow events can, however, create a more complex transport path, highlighting the importance

of ice-flow history reconstructions. Compared to basal till, the transport distance of ablation till is longer and the depositional history more complex. Ablation till consists of material transported within and on top of a glacier. It is deposited by passive melt out processes. Deposition of ablation till adjacent to remnant ice-blocks produces an irregular, undulating to hummocky topography. Ablation till is a less compact diamicton. It contains more gravel and has a sandier matrix (Figure 4). It can be massive to crudely stratified and may contain lenses of sorted sand and gravel. Formed by ice downwasting during deglaciation, ablation tills are typically exposed at the surface and can overlie basal tills.

spatial and genetic association of basal till with other surficial materials and their depositional



as pedogenesis. High potential (3) map units are mostly basal till with lesser amounts of another surface material (excluding ablation till). Knowledge of the surface expression of this

Moderate potential is assigned to map units containing varying amounts of basal till and ablation till. These map units typically represent (4) thick basal till deposits in depressions or small valleys where ablation till has been deposited, or (5) near the margins of areally extensive ablation till map units where basal till may be found within a few metres of surface or in areas of higher elevation (i.e., where ablation till thins).

Low potential (6) is assigned to map units that are predominantly another surface material. These areas may include basal till deposits that are too small or discontinuous to resolve at the current map scale. Poor potential (7) is assigned where thick ablation till overlies basal till. These areas typically consist of hummocky ablation till and may include lesser amounts of another surficial material (e.g., ice-contact glaciofluvial deposits). These areas are still mapped as having basal till potential because exposures of sufficient depth could expose underlying

ACKNOWLEDGEMENTS L.B. Aspler and A.S. Hickin are thanked for their review of this map.

Surficial material other than till.

Clifford, A., and Hart, C.J.R., 2014. Targeting Resources through Exploration and Knowledge (TREK): Geoscience BC's newest minerals project, Interior Plateau Region, central British Columbia (NTS 093B, C, F, G). In: Geoscience BC Summary of Activities 2013, Geoscience BC, Report 2014-1, pp. 13-18.

Deblonde, C., Plouffe, A., É. Boisvert, Buller, G., Davenport, P., Everett, D., Huntley, D., Inglis, E., Kerr, D., Moore, A., Paradis, S.J., Parent, M., Smith, I.R., St. Onge, D., and Weatherston, A., 2012. Science language for an integrated Geological Survey of Canada data model for surficial geology maps, version 1.2. Geological Survey of Canada, Open File 7003, 224 p.

Diakow, L.J., van der Heyden, P., and Metcalfe, P., 1997. Introduction. In: Diakow, L.J., Newell, J.M. and Metcalfe, P. (Eds.). Interior Plateau Geoscience Project: summary of geological, geochemical, and geophysical studies, BC Ministry of Energy and Mines, British Columbia Geological Survey Paper 1997-2, Geological Survey of Canada, Open File 3448, pp.

Ferbey, T, Arnold, H., and Hickin, A.S., 2013. Ice-flow indicator compilation, British Columbia. British Columbia Ministry of Energy and Mines, British Columbia Geological Survey Open File 2013-06, 1:1 650 000 scale.

Holland, S.S., 1976. Landforms of British Columbia: a physiographic outline. British Columbia Ministry of Energy and Mines, and Petroleum Resources, British Columbia Geological Survey

Levson, V.M., 2001a. Quaternary geology of the Babine porphyry copper district: implications for geochemical exploration. Canadian Journal of Earth Sciences, 38, 733-749. Levson, V.M., 2001b. Regional till geochemical surveys in the Canadian Cordillera: sample

media, methods, and anomaly evaluation. In: McClenaghan, M.B., Bobrowsky, P.T., Hall, G.E.M. and Cook, S.J. (Eds.), Drift Exploration in Glaciated Terrain, Geological Society,

Special Publication 185, pp. 45–68.

Levson, V.M., and Giles, T.R., 1997. Quaternary geology and till geochemistry studies in the Nechako and Fraser plateaus, central British Columbia (NTS 93 C/1, 8, 9, 10; F/2, 3, 7; L/16; M/1). In: Diakow, L.J., Newell, J.M. and Metcalfe, P. (Eds.), Interior Plateau Geoscience Project: summary of geological, geochemical, and geophysical studies, BC Ministry of Energy and Mines, British Columbia Geological Survey Paper 1997-2, Geological Survey of Canada,

Logan, J.M., 2013. Porphyry systems of central and southern BC: an overview and field trip road log. In: Logan, J.M., and Schroeter, T.G. (Eds.), Porphyry systems of central and southern BC: tour of central BC porphyry deposits from Prince George to Princeton, Society of Economic Geologists, Guidebook Series 44, pp. 1-45.

Miller, J.K., 1984. Model for clastic indicator trains in till. In: Prospecting in Areas of Glaciated Terrain, Institution of Mining and Metallurgy, London, pp. 69–77.

Proudfoot, D.N., Bobrowsky, P.T., and Meldrum, D.G., 1995. Drift exploration potential maps derived from terrain geology maps. In: Bobrowsky, P.T., Sibbick, S.J., Newell, J.M., and Matysek, P.F. (Eds.), Drift Exploration in the Canadian Cordillera, British Columbia Ministry of Energy and Mines, British Columbia Geological Survey Paper 1995-2, pp. 23-31.

Sacco, D.A., Jackaman, W., and Ferbey, T., 2014. Targeted geochemical and mineralogical surveys in the TREK Project area, central British Columbia (parts of NTS 093B, C, F, G). In: Geoscience BC Summary of Activities 2013, Geoscience BC Report 2014-1, pp. 19–34.

Shilts, W., 1993. Geological Survey of Canada's contributions to understanding the

composition of glacial sediments. Canadian Journal of Earth Sciences, 30, 333–353. Struik, L.C., and MacIntyre, D.G., 2001. Introduction to the special issue of Canadian Journal of Earth Sciences: the Nechako NATMAP project of the central Canadian Cordillera. Canadian Journal of Earth Sciences, 38, 485-494.

occurred. Consist of hillocks and hollows with slopes ≤ 15°. **BASAL TILL POTENTIAL**

North American Datum 1983 Shuttle Radar Topography Mission (SRTM) DEM, 3, arcsecond (90 m) resolution

Interior Plateau that focused on regional geological

completed for the planning and implementation | CROSS SECTIONS be released in future publications. Surficial sediment geochemical and mineralogical

anomalies can be used to locate buried bedrock mineralization. Sediments with a relatively simple transport and depositional history, such as basal tills, are better suited for mineral exploration. Basal till is ideal for assessing mineral potential because: 1) it is a common sediment in glaciated terrain; 2) it can be considered a first derivative of bedrock (Shilts, 1993) and therefore has a similar geochemical signature to its bedrock source; 3) its transport motor, and 4) it determined by local ice-flow reconstructions; and 4) it vertical vertical exaggeration 11x its bedrock source; 3) its transport history can be extensive than the bedrock source (Levson, 2001b) Glacial transport and deposition of basal till produces a dispersal train, elongated down ice from its parent rock (Figure 1).

materials and their topographic expression.

Basal till is eroded, transported and deposited at the base of an active glacier. It typically has a subdued surface expression that either follows underlying topography (as a blanket or veneer) or is streamlined in the direction of ice flow. It is a dense, unsorted, massive, matrix-supported diamicton, with a matrix consisting mainly of silt and clay with lesser amounts of sand (Figure 3). Vertical joint and subhorizontal fissility intersections can give basal till a blocky appearance. Clasts are mostly gravel-sized and subangular to subrounded, and are commonly striated. The transport path of basal till is relatively simple and short and can be established by measuring the azimuth of ice-flow indicators, also produced in the subglacial environment. Multiple

Each mapped till unit is assigned a basal till potential rating. This is assignment is based on the

environments. It should be noted that appropriate sample material might be found in low

potential areas. For example, windows through an ablation till overlying a basal till, may be

High potential is assigned to units containing mainly basal till. The highest potential category

(1) includes till blankets (>2 m thick) and streamlined till with some till veneer (<2 m thick). In

these map units, samples can be collected from most exposures. In the second category of

high potential (2), basal till veneers are predominant and likely include some bedrock

exposures. In these areas, sample collection may be most productive down-ice from bedrock

outcrop, where till might be sufficiently thick to avoid post-depositional surface processes such

material, is unlikely to occur at surface in areas designated as 'none'.

Figure 3. Ablation till exposed in road cut (65 cm pick for scale both photos). There is a higher percentage of sand and gravel, compared to a typical basal till (see Figure 2), and lower density.